

Appl. No. 10/525,451  
Amdt. Dated of May 26, 2008  
Reply to Office action of January 29, 2008

**Amendments to the claims**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claims 1 (currently amended). In a receiver of a communication system, a method for reducing noise in a transformed signal, said transformed signal having a plurality of signal components on different subcarriers which are orthogonal to each other, said method comprising the steps of:

receiving a the transformed signal by a detector of said communication system;

processing the plurality of signal components of said transformed signal, wherein said processing step comprises:

identifying one or more signal components having one or more smallest channel coefficients based upon a channel estimate of said plurality of signal components; and

Appl. No. 10/525,451  
Amdt. Dated of May 26, 2008  
Reply to Office action of January 29, 2008

reconstructing a predetermined number of times, by a reconstructing module, said one or more signal components of said plurality of signal components, said reconstructing being based upon said processing step to thereby reduce noise in said transformed signal; and

replacing said one or more signal components with the reconstructed one or more signal components to provide a reconstructed transformed signal having one or more reconstructed signal components ~~wherein said processing step further comprises the steps: identifying said one or more signal components based upon a channel estimate of said plurality of signal components; and further wherein said reconstructing step further comprises the step of providing a reconstructed transformed signal of said transformed signal.~~

Claim 2 (original). The method as claimed in claim 1, wherein said processing step comprises the step of providing an estimated signal from said transformed signal at output of said detector and based upon said channel estimate.

Claim 3 (original). The method as claimed in claim 2, wherein said processing step further comprises the step of decision processing said estimated

Appl. No. 10/525,451  
Amdt. Dated of May 26, 2008  
Reply to Office action of January 29, 2008

signal using a plurality of decision modules.

Claim 4 (original). The method as claimed in claim 3, wherein said decision processing step comprises the step of soft decision processing.

Claim 5 (original). The method as claimed in claim 3, wherein said decision processing step comprises the step of hard decision processing.

Claim 6 (original). The method as claimed in claim 1, wherein said reconstructing step further comprises the step of providing another estimated signal from said reconstructed transformed signal at said output of said detector and based upon said channel estimate.

Claim 7 (original). The method as claimed in claim 6, wherein said processing step further comprises the step of decision processing said another estimated signal using said plurality of decision modules.

Claim 8 (original). The method as claimed in claim 7, wherein said decision processing of said another estimated signal comprises the step of soft decision

Appl. No. 10/525,451  
Amdt. Dated of May 26, 2008  
Reply to Office action of January 29, 2008

processing.

Claim 9 (original). The method as claimed in claim 7, wherein said decision processing of said another estimated signal comprises the step of hard decision processing.

Claim 10 (original). The method as claimed in claim 7, wherein said reconstructing step further comprises the step of determining whether said one or more signal components has been reconstructed said predetermined number of times

Claim 11 (original). The method as claimed in claim 10, wherein said reconstructing step further comprises the step of determining whether to process another one or more signal components of said plurality of signal components.

Claim 12 (original). The method as claimed in claim 11, and further comprising the step of providing current estimated signal for subsequent processing when determined that iteration of said another signal component is

Appl. No. 10/525,451  
Amdt. Dated of May 26, 2008  
Reply to Office action of January 29, 2008  
not required.

Claim 13 (original). The method as claimed in claim 11, wherein said reconstructing step further comprises the step of simultaneously reconstructing two or more of said another one or more signal components.

Claim 14 (original). The method as claimed in claim 11, wherein said reconstructing step further comprises the step of reconstructing, one at a time, each of said another one or more signal components.

Claim 15 (original). The method as claimed in claim 1, wherein said reconstructing step further comprises the step of simultaneously reconstructing two or more of said one or more signal components.

Claim 16 (original). The method as claimed in claim 1, wherein said reconstructing step further comprises the step of reconstructing, one at a time, each of said one or more signal components.

Claim 17 (currently amended). A receiver for reducing noise in a transformed

Appl. No. 10/525,451  
Amdt. Dated of May 26, 2008  
Reply to Office action of January 29, 2008

signal, said transformed signal having a plurality of signal components on  
different subcarriers which are orthogonal to each other, said receiver  
comprising:

a signal reconstructing section having:

a detector for detecting said transformed signal;

one or more decision modules, each of said one or more decision  
modules having an input coupled to output of said detector; and

a reconstructing module having one or more inputs, said one or  
more inputs being respectively coupled to output of said one or more  
decision modules,

wherein said reconstructing module is adapted to identify one or  
more signal components having one or more smallest channel  
coefficients based upon a channel estimate of said plurality of signal  
components;

wherein said ~~reconstructing module is adapted to reconstruct~~ one  
or more signal components of said plurality of signal components are  
reconstructed a predetermined number of times to provide a  
reconstructed transformed signal having one or more transformed signal  
components; and

Appl. No. 10/525,451  
Amdt. Dated of May 26, 2008  
Reply to Office action of January 29, 2008

the one or more signal components are replaced with the  
reconstructed one or more transformed signal components to thereby  
form a noise-reduced transformed signal; ~~and wherein said~~  
~~reconstructing module is adapted to provide a reconstructed transformed~~  
~~signal of said transformed signal; further wherein said reconstructing~~  
~~module is adapted to identify said one or more signal components based~~  
~~upon a channel estimate of said plurality of signal components.~~

Claim 18 (original). The receiver as claimed in claim 17, wherein said one or more decision modules comprises one or more hard decision modules.

Claim 19 (original). The receiver as claimed in claim 17, wherein said one or more decision modules further comprises one or more soft decision modules.

Claim 20 (original). The receiver as claimed in claim 17, wherein said reconstructing module is adapted to perform reconstruction based on a relationship between a received signal component and a transmitted signal.

Claim 21 (original). The receiver as claimed in claim 17, wherein said

Appl. No. 10/525,451  
Amdt. Dated of May 26, 2008  
Reply to Office action of January 29, 2008

reconstructing module is adapted to perform simultaneous reconstruction of two or more of said one or more signal components.

Claim 22 (original). The receiver as claimed in claim 17, wherein said reconstructing module is adapted to perform reconstruction of said one or more signal components signal components one at a time.

Claim 23 (currently amended). A communication system comprising:

a signal reconstructing section for reducing noise in a transformed signal, said transformed signal having a plurality of signal components\_ on different subcarriers which are orthogonal to each other, said signal reconstructing section having:

a detector for detecting said transformed signal;

one or more decision modules, each of said one or more decision modules having an input coupled to output of said detector; and

a reconstructing module having one or more inputs, said one or more inputs being respectively coupled to output of said one or more decision modules,



Appl. No. 10/525,451  
Amdt. Dated of May 26, 2008  
Reply to Office action of January 29, 2008

wherein said reconstructing module is adapted to identify  
one or more signal components having one or more smallest  
channel coefficients based upon a channel estimate of said  
plurality of signal components;

~~wherein said reconstructing module is adapted to~~  
~~reconstruct~~ one or more signal components of said plurality of  
signal components are reconstructed by a predetermined number  
of times to provide a reconstructed transformed signal having one  
or more transformed signal components; and

the one or more signal components are replaced with the  
reconstructed one or more transformed signal components to  
thereby form a noise-reduced transformed signal;—

~~wherein said reconstructing module is adapted to provide a~~  
~~reconstructed transformed signal of said transformed signal;—~~

~~further wherein said reconstructing module is adapted to~~  
~~identify said one or more signal components based upon a channel~~  
~~estimate of said plurality of signal components.~~

Appl. No. 10/525,451  
Amdt. Dated of May 26, 2008  
Reply to Office action of January 29, 2008

Claim 24 (original). The communication system as claimed in claim 23,  
wherein said one or more decision modules comprises one or more hard  
decision modules.

Claim 25 (original). The communication system as claimed in claim 23,  
wherein said one or more decision modules further comprises one or more soft  
decision modules.

Claim 26 (original). The communication system as claimed in claim 23,  
wherein said reconstructing module is adapted to perform reconstruction based  
on a relationship between a received signal component and a transmitted signal.

Claim 27 (original). The communication system as claimed in claim 23,  
wherein said reconstructing module is adapted to perform simultaneous  
reconstruction of two or more of said one or more signal components.

Claim 28 (original). The communication system as claimed in claim 23,  
wherein said reconstructing module is adapted to perform reconstruction of said  
one or more signal components signal components one at a time.

Appl. No. 10/525,451  
Amdt. Dated of May 26, 2008  
Reply to Office action of January 29, 2008

Claim 29 (currently amended). A signal reconstructing section for a receiver to reduce noise in a transformed signal, said transformed signal having a plurality of signal components on different subcarriers which are orthogonal to each other, said signal reconstructing section comprising:

a detector for detecting said transformed signal;

one or more decision modules, each of said one or more decision modules having an input coupled to output of said detector; and

a reconstructing module having one or more inputs, said one or more inputs being respectively coupled to output of said one or more decision modules,

wherein said reconstructing module is adapted to identify one or more signal components having one or more smallest channel coefficients based upon a channel estimate of said plurality of said components;

wherein said ~~reconstructing module is adapted to reconstruct~~ one or more signal components of said plurality of signal components are reconstructed by a predetermined

Appl. No. 10/525,451  
Amdt. Dated of May 26, 2008  
Reply to Office action of January 29, 2008

number of times to provide a reconstructed transformed  
signal having one or more transformed signal components;  
and  
the one or more signal components are replaced with  
the reconstructed one or more transformed signal  
components to thereby form a noise-reduced transformed  
signal.—

~~wherein said reconstructing module is adapted to~~  
~~provide a reconstructed transformed signal of said~~  
~~transformed signal;—~~

~~further wherein said reconstructing module is~~  
~~adapted to identify said one or more signal components~~  
~~based upon a channel estimate of said plurality of signal~~  
~~components.~~

Claim 30 (original). The signal reconstructing section as claimed in claim 29,  
wherein said one or more decision modules comprises one or more hard  
decision modules.

Appl. No. 10/525,451  
Amdt. Dated of May 26, 2008  
Reply to Office action of January 29, 2008

Claim 31 (original). The signal reconstructing section as claimed in claim 29, wherein said one or more decision modules further comprises one or more soft decision modules.

Claim 32 (original). The signal reconstructing section as claimed in claim 29, wherein said reconstructing module is adapted to perform reconstruction based on a relationship between a received signal component and a transmitted signal.

Claim 33 (original). The signal reconstructing section as claimed in claim 29, wherein said reconstructing module is adapted to perform simultaneous reconstruction of two or more of said one or more signal components.

Claim 34 (original). The signal reconstructing section as claimed in claim 29, wherein said reconstructing module is adapted to perform reconstruction of said one or more signal components signal components one at a time.